

Product information

Motorbike 4T Bike-Additive

PI 12/30/04/2015



Description

Increases engine performance. Removes deposits in the fuel system, in valves, spark plugs and in the combustion chamber and prevents renewed formation. That also reduces fuel consumption. Protects the entire fuel system from corrosion. Prevents carburetor icing. Cat tested.

Properties

- optimizes engine performance
- protects fuel system against corrosion
- reduces residues
- environmentally friendly
- tested for catalytic converters
- increases operational reliability
- for carburetor and fuel-injection engines
- highly economical
- reduces the risk of knocking combustion
- normalizes gasoline consumption and exhaust emissions values



Available pack sizes

125 ml Can sheet metal	1581 D-GB-I
125 ml Can sheet metal	5918 D-F-I-GR

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	41 °C
Pour point	- 45 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,796 g/cm ³

Areas of application

Added to fuel for all four-stroke motorbike engines (aspirated and injection).

Application

125 ml Motorbike 4T Bike-Additive is sufficient for 15 to 20 litres of fuel. Add every time you fill up.